



Continental Device India Pvt. Limited

An IATF 16949, ISO9001 and ISO 14001 Certified Company



Three Terminal Positive Voltage Regulator

TL7805K



TO-3

TO-3
Leaded Plastic
Package
RoHS compliant

FEATURES:

1. Output current in excess of 1.5A
2. Output voltage of 5V
3. Internal thermal overload protection
4. Output transition Safe-Area compensation
5. Minimum Lot-to-Lot variations for robust device performance and reliable operation

ABSOLUTE MAXIMUM RATINGS ($T_a = 25\text{ }^\circ\text{C}$)

PARAMETER	SYMBOL	VALUE	UNIT
DC input voltage	V_i	35	V
Output current	I_o	Internally limited	
Power dissipation	P_{tot}	Internally limited	
Operating junction temperature	T_{OP}	-40 to 125	$^\circ\text{C}$
Storage temperature	T_{stg}	-55 to 150	$^\circ\text{C}$

THERMAL CHARACTERISTICS

Thermal Resistance, Junction to Case	$R_{\theta j-c}$	2	$^\circ\text{C/W}$
Thermal Resistance, Junction to Ambient	$R_{\theta j-a}$	50	$^\circ\text{C/W}$

ELECTRICAL CHARACTERISTICS

($V_i = 10\text{V}$, $I_o = 0.5\text{A}$, $C_i = 0.33\mu\text{F}$, $C_o = 0.1\mu\text{F}$ unless otherwise specified)

PARAMETER	SYMBOL	TEST CONDITIONS	MIN	MAX	UNIT
Output Voltage	V_o	$V_{in} = 20\text{V}$; $I_o = 500\text{mA}$	4.8	5.2	V
Line Regulation	ΔV_V	$7.5\text{V} \leq V_{in} \leq 20\text{V}$; $I_o = 0.5\text{A}$	-	50	mV
Load Regulation	ΔV_i	$5.0\text{mA} \leq I_o \leq 1.5\text{A}$; $V_{in} = 10\text{V}$	-	100	mV
Quiescent Current	I_q	$V_{in} = 10\text{V}$; $I_o = 1.5\text{A}$	-	6	mA
Quiescent Current Change	$\Delta q1$	$5.0\text{mA} \leq I_o \leq 1.0\text{A}$; $V_{in} = 10\text{V}$	-	0.5	mA
Quiescent Current Change	$\Delta q2$	$7\text{V} \leq V_{in} \leq 25\text{V}$; $I_o = 500\text{mA}$	-	1.3	mA

TL7805K
Rev1_07032020EID




Continental Device India Pvt. Limited

An IATF 16949, ISO9001 and ISO 14001 Certified Company



PACKGE DETAILS

TO-3



PIN CONFIGURATION:

1. INPUT
2. GROUND
3. OUTPUT



Continental Device India Pvt. Limited

An IATF 16949, ISO9001 and ISO 14001 Certified Company



Recommended Product Storage Environment for Discrete Semiconductor Devices

This storage environment assumes that the Diodes and transistors are packed properly inside the original packing supplied by CDIL.

- Temperature 5 °C to 30 °C
- Humidity between 40 to 70 %RH
- Air should be clean.
- Avoid harmful gas or dust.
- Avoid outdoor exposure or storage in areas subject to rain or water spraying .
- Avoid storage in areas subject to corrosive gas or dust. Product shall not be stored in areas exposed to direct sunlight.
- Avoid rapid change of temperature.
- Avoid condensation.
- Mechanical stress such as vibration and impact shall be avoided.
- The product shall not be placed directly on the floor.
- The product shall be stored on a plane area. They should not be turned upside down. They should not be placed against the wall.

Shelf Life of CDIL Products

The shelf life of products is the period from product manufacture to shipment to customers. The product can be unconditionally shipped within this period. The period is defined as 2 years.

If products are stored longer than the shelf life of 2 years the products shall be subjected to quality check as per CDIL quality procedure.

The products are further warranted for another one year after the date of shipment subject to the above conditions in CDIL original packing.

Floor Life of CDIL Products and MSL Level

When the products are opened from the original packing, the floor life will start.

For this, the following JEDEC table may be referred:

JEDEC MSL Level		
Level	Time	Condition
1	Unlimited	≤30 °C / 85% RH
2	1 Year	≤30 °C / 60% RH
2a	4 Weeks	≤30 °C / 60% RH
3	168 Hours	≤30 °C / 60% RH
4	72 Hours	≤30 °C / 60% RH
5	48 Hours	≤30 °C / 60% RH
5a	24 Hours	≤30 °C / 60% RH
6	Time on Label(TOL)	≤30 °C / 60% RH



Continental Device India Pvt. Limited

An IATF 16949, ISO9001 and ISO 14001 Certified Company



Customer Notes

Component Disposal Instructions

1. CDIL Semiconductor Devices are RoHS compliant, customers are requested to please dispose as per prevailing Environmental Legislation of their Country.
2. In Europe, please dispose as per EU Directive 2002/96/EC on Waste Electrical and Electronic Equipment (WEEE).

Disclaimer

The product information and the selection guides facilitate selection of the CDIL's Semiconductor Device(s) best suited for application in your product(s) as per your requirement. It is recommended that you completely review our Data Sheet(s) so as to confirm that the Device(s) meet functionality parameters for your application. The information furnished in the Data Sheet and on the CDIL Web Site/CD are believed to be accurate and reliable. CDIL however, does not assume responsibility for inaccuracies or incomplete information. Furthermore, CDIL does not assume liability whatsoever, arising out of the application or use of any CDIL product; neither does it convey any license under its patent rights nor rights of others. These products are not designed for use in life saving/support appliances or systems. CDIL customers selling these products (either as individual Semiconductor Devices or incorporated in their end products), in any life saving/support appliances or systems or applications do so at their own risk and CDIL will not be responsible for any damages resulting from such sale(s).

CDIL strives for continuous improvement and reserves the right to change the specifications of its products without prior notice.



CDIL is a registered trademark of

Continental Device India Pvt. Limited

C-120 Naraina Industrial Area, New Delhi 110 028, India.

Telephone +91-11-2579 6150, 4141 1112 Fax +91-11-2579 5290, 4141 1119

email@cdil.com www.cdil.com

CIN No. U32109DL1964PTC004291

TL7805K
Rev1_07032020EID